FORD TRUCKS 1845T EURO6

Basic Features						
/ehicle Type			Tractor			
Axle			4x2			
Emission		Euro 6				
Cabin Type		Extra High Roof Sleeper Cab				
Wheelbase (mm)		3600				
Ingine						
Туре			Ecotorq 12.7 lt			
Displacement (cc)		12740				
Bore x Stroke		130 mm x 160 mm				
Power		450 PS (353 kW) / 1800 RPM				
ōrque		2300 Nm / 900-1300 RPM				
Compression Ratio		17 +/- 0,5 : 1				
Dil Filling Volume		50 L				
Coolant Volume		57 L (77 L with Intarder)				
Transmission						
Clutch			430 mm Single Disc			
Manuel Transmission / Ratios (1. ge	ear - 16. gear)	ZF 16S 2530 (13,805 - 0,836)				
Automated Transmission / Ratios (0,		Ecotorg 16S 2600 DD AMT (1			
Steering	i Bear io Bear)			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
Steering				N 11		
			Power Assisted Single C	Lircuit		
Chassis						
Chassis Thickness			10 mm			
Chassis Strength		500 MPa				
Suspension (Front / Rear)		90 mm Parabolic Leaf Springs / Air Suspension				
Axle		Single Reduction				
Wheel Rim		Steel Wheel (22,5 x 9)				
Tyre Information						
i. Teker Yüksekliği	FDR	Tyre	5th Wheel Height (Laden)	5th Wheel Height (Unladen)		
100 mm	2,47 - 2,64	315/70 R22.5	1121 mm	1147 mm		
150 mm	2,64 - 3,08	295/80 R22,5	1167 mm	1196 mm		
200 mm	2,64 - 3,08	295/80 R22,5	1200 mm	1225 mm		
200 mm	2,64 - 3,08	315/80 R22,5	1227 mm	1307 mm		
250 mm	2,64 - 3,08	295/80 R22,5	1270 mm	1289 mm		
250 mm	2,64 - 3,08	315/80 R22,5	1274 mm	1350 mm		
Braking System						
Brakes (Ømm x mm Length)			430 x 45 - Disc Brak	es		
Braking System		Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Engine Brake Power		max. 320 kW (Engine Level)				
ntarder Power		max. 450 kW / continuous 160 kW				
lectrical System			225 Ah			
Battery			130 A / 6,5 kW			
Battery Ilternator / Starter Motor						
Battery Ilternator / Starter Motor						
Electrical System Battery Alternator / Starter Motor Fanks Fuel Tank			600 L Aluminium			



Sharing the load

Dimensions (mm)					
5 th Wheel Height		1200			
Front Overhang		1500			
Wheelbase		3600			
Overall Length		5975			
Overall Cab Length		2312			
Total Height	3947 (Extra High Roof) - 3064 (Low Roof)				
Overall Vehicle Width (Excluding Mirrors)		2541			
Chassis Width		866			
Rear Overhang		875			
Chassis Height-Front		1001			
Chassis Height-Rear		990			
Ground Clearance-Front		286			
Ground Clearance-Rear		223			
Turning Radius		7500			
Weights (kg)	1. Axle	2. Axle	Total		
Technically Permissible Weights	7500	12600	19000		
Kerb Weight	5460	2538	7998		
Payload	2040	10062	10002		
GVM (Legal)	7100	11500	18000		

STANDARD EQUIPMENT

Air Conditioner

- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Extra High Roof Cab with Double Bed
- Dry Type Cab Heater
- Cab Air Suspension
- Cruise Control
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar SupportElectrically Operated Sunroof
- Front and Rear Vehicle Antiroll Bars
- Profit and Real vehicle Af
 Disc Brakes
- Electronic Brake System (EBS) and Anti-Lock Brake System (ABS)
- Electronic Brake Force Control
- Brake Assistant
- Electronic Stability Control (ESP)
- Pad Wear Indicator
- Immobilizer
- Home Safe and Approach Lights
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Variable Steering Pump for Improved Fuel Economy
- Hill Launch Assist
- Coupling Force Control
- Front Fog Lamps
- Axle Load Indicator
- DAB Radio**
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert, Pre-Collision Assist)

OPTIONAL EQUIPMENT

- Automated Transmission (With Different Usage Modes)
- Intarder
- ADR Package
- Low Roof Sleeper Cab with Single Bed
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater
- Electrically Operated Cab Tilting
- Engine Driven PTO
- Transmission Driven PTO
- 5th Wheel Options*: 1100, 1150, 1200, 1250, mm
- Side Mounted Tyre Carrier
- Jost 5th Wheel
- Dual Fuel Tank (600 L + 450 L)
- Side Skirt
- Spoiler*
- Electrically Operated Cab Tilting
- Auto Light Sensor
- Rain Sensor
- Less Spare Tire
- Technology Pack (Auto High-Beam Headlamps, Pre-Collision Assist with Pedestrian Detection, Intelligent Adaptive Cruise Control with Stop&Go ***)

* Not available with Low Roof Sleeper Cab Version ** DAB Radio can be standard or optional according to the market. ***Only available with Automated Transmission.

This leaflet includes products designed for Ford Trucks vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.